

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Bondtec STP 75**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Adhesive  
Assembly material

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Fola Abfülltechnik GmbH  
Industriestraße 55  
D-40822 Mettmann  
Tel.: +49 2104 28680-10  
Fax: +49 2104 28680-20  
www.fola-abfuelltechnik.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (WIC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
Aquatic	3	H412-Harmful to aquatic life with long lasting effects.
Chronic		

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**



Warning

H319-Causes serious eye irritation. H412-Harmful to aquatic life with long lasting effects.

P280-Wear eye protection.  
P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313-If eye irritation persists: Get medical advice / attention.

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

### SECTION 3: Composition/information on ingredients

#### 3.1 Substance

n.a.

#### 3.2 Mixture

<b>Trimethoxyvinylsilane</b>	
Registration number (REACH)	01-2119513215-52-XXXX
Index	---
EINECS, ELINCS, NLP	220-449-8
CAS	2768-02-7
content %	1-5
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226 Acute Tox. 4, H332
<b>3-(trimethoxysilyl)propylamine</b>	
Registration number (REACH)	01-2119510159-45-XXXX
Index	---
EINECS, ELINCS, NLP	237-511-5
CAS	13822-56-5
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315 Eye Dam. 1, H318
<b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate</b>	
Registration number (REACH)	01-2119978231-37-XXXX

Index	---
EINECS, ELINCS, NLP	264-513-3
CAS	63843-89-0
content %	0,025-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP)	Acute Tox. 4, H302 STOT RE 1, H372 (lymph nodes, liver, spleen) Aquatic Chronic 1, H410 (M=10)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
The substances named in this section are given with their actual, appropriate classification!  
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

##### Inhalation

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.

##### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent  
Thinners

##### Eye contact

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

##### Ingestion

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

n.c.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

CO2  
Extinction powder  
Water jet spray  
Large fire:

Water jet spray / alcohol resistant foam

##### Unsuitable extinguishing media

None known

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon  
Oxides of sulphur  
Toxic gases

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.  
Avoid contact with eyes or skin.  
If applicable, caution - risk of slipping.

#### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
Prevent from entering drainage system.  
If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Or:

Pick up mechanically and dispose of according to Section 13.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

##### 7.1.1 General recommendations

Ensure good ventilation.  
Avoid contact with eyes.  
Avoid long lasting or intensive contact with skin.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.

##### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
Store product closed and only in original packing.  
Not to be stored in gangways or stair wells.

Store cool.

Store in a dry place.

#### 7.3 Specific end use(s)

No information available at present.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

The methanol listed below can arise upon contact with water.

Chemical Name	Content %
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust)	WEL-STEL: --- ---
Monitoring procedures:	---

BMGV: --- Other information: ---

Chemical Name	Methanol	Content %:
WEL-TWA: 200 ppm (266 mg/m <sup>3</sup> ) (WEL), 200 ppm (260 mg/m <sup>3</sup> ) (EU)	WEL-STEL: 250 ppm (333 mg/m <sup>3</sup> ) (WEL)	---
Monitoring procedures:		
<ul style="list-style-type: none"> <li>- Compur - KITA-119 SA (549 640)</li> <li>- Compur - KITA-119 U (549 657)</li> <li>- Draeger - Alcohol 25/a Methanol (81 01 631)</li> <li>- DFG (D) (Lösungsmittelgemische 6), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 65-1 (2004)</li> <li>- Draeger - Alcohol 100/a (CH 29 701)</li> </ul>		
BMGV: ---	Other information: Sk (WEL, EU)	

**Trimethoxyvinylsilane**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,4	mg/l	Für entsprechen des Silantrio (Hydrolysprodukt) ermitte lt.
	Environment - marine		PNEC	0,04	mg/l	Für entsprechen des Silantrio (Hydrolysprodukt) ermitte lt.
	Environment - water, sporadic (intermittent) release		PNEC	2,4	mg/l	Für entsprechen des Silantrio (Hydrolysprodukt) ermitte lt.
	Environment - sewage treatment plant		PNEC	6,6	mg/l	Für entsprechen des Silantrio (Hydrolysprodukt) ermitte lt.
	Environment - sediment, freshwater		PNEC	1,5	mg/kg dw	Für entsprechen des Silantrio (Hydrolysprodukt) ermitte lt.
	Environment - sediment, marine		PNEC	0,15	mg/kg dw	Für entsprechen des Silantrio (Hydrolysprodukt) ermitte lt.
	Environment - soil		PNEC	0,06	mg/kg dw	Für entsprechen des Silantrio (Hydrolysprodukt) ermitte lt.
Consumer	Human - dermal	Short term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,7	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,1	mg/kg bw/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	93,4	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,2	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	2,6	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	4,9	mg/m <sup>3</sup>	

**3-(trimethoxysilyl)propylamine**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
---------------------	--	------------------	------------	-------	------	------

	Environment - freshwater		PNEC	0,33	mg/l	
	Environment - marine		PNEC	0,03 3	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,3	mg/l	
	Environment - sediment, freshwater		PNEC	1,2	mg/kg dry weight	
	Environment - sediment, marine		PNEC	0,12	mg/kg dry weight	
	Environment - soil		PNEC	0,04 5	mg/kg dry weight	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	17	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	5	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	5	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	17,4	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	58	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	8,3	mg/kg bw/d	

**Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [(3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl)methyl]butylmalonate**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0	mg/l	
	Environment - marine		PNEC	0	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,61	mg/l	
	Environment - sediment, freshwater		PNEC	504, 4	mg/kg dry weight	
	Environment - sediment, marine		PNEC	50,4 4	mg/kg dry weight	
	Environment - soil		PNEC	1	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,01	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,03 3	mg/kg body weight/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,00 3	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m <sup>3</sup>	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,07	mg/kg bw/day	

**Calcium carbonate**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - sewage treatment plant		PNEC	100	mg/l	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,1	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	1,06	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4,26	mg/m <sup>3</sup>	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10	mg/m <sup>3</sup>	

**Methanol**

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment, freshwater		PNEC	570, 4	mg/kg	
	Environment - sediment, marine		PNEC	57,0 4	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	154 0	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - freshwater		PNEC	20,8	mg/l	
	Environment - marine		PNEC	2,08	mg/l	
	Environment - sediment		PNEC	77	mg/kg	
	Environment - sediment		PNEC	7,7	mg/kg	
Consumer	Human - inhalation	Short term, local effects	DNEL	50	mg/m <sup>3</sup>	
Consumer	Human - inhalation	Long term, local effects	DNEL	50	mg/m <sup>3</sup>	
Consumer	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m <sup>3</sup>	
Consumer	Human - oral	Short term, systemic effects	DNEL	8	mg/kg body weight/day	

Consumer	Human - dermal	Long term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	50	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	8	mg/kg body weight/day	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	40	mg/kg body weight/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	260	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg body weight/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	260	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	260	mg/m3	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40, AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0.002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40, BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage. \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE). (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

**8.2 Exposure controls**  
**8.2.1 Appropriate engineering controls**

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. BS EN 14042.  
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

**8.2.2 Individual protection measures, such as personal protective equipment**

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.  
 Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).  
 Skin protection - Hand protection:  
 Chemical resistant protective gloves (EN 374).  
 Recommended  
 Protective nitrile gloves (EN 374).  
 Minimum layer thickness in mm:  
 >= 0,35  
 Permeation time (penetration time) in minutes:  
 >= 120  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.  
 Protective hand cream recommended.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 Normally not necessary.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.  
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
 Selection of materials derived from glove manufacturer's indications.  
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

**8.2.3 Environmental exposure controls**

No information available at present.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

Physical state:	Pastelike, Liquid
Colour:	According to specification
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	Not determined
Evaporation rate:	n.a.
Flammability (solid, gas):	n.a.

Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	~1,6 g/cm3 (20°C)
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	n.a.
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No
<b>9.2 Other information</b>	
Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined
Metal content:	Not determined
Molar mass:	Not determined
Chemical heat of combustion:	Not determined

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**  
 The product has not been tested.  
**10.2 Chemical stability**  
 Stable with proper storage and handling.  
**10.3 Possibility of hazardous reactions**  
 reacts with water  
**10.4 Conditions to avoid**  
 See also section 7.  
 Strong heat  
 Moisture  
**10.5 Incompatible materials**  
 See also section 7.  
 None known  
**10.6 Hazardous decomposition products**  
 See also section 5.2  
 In case of contact with water:  
 Methanol

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**  
 Possibly more information on health effects, see Section 2.1 (classification).

Bondtec STP 75						
Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Trimethoxyvinylsilane						
Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:	LD50	7120	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	3200	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	2773	ppm/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Acute toxicity, by inhalation:	LC50	16,8	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Slightly irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:						Negative

Reproductive toxicity:	NOAEL	1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	10	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	Vapours
Symptoms:						drowsiness, dizziness, nausea, abdominal pain, breathing difficulties, visual disturbances

3-(trimethoxysilyl)propylamine						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>10000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Risk of serious damage to eyes.
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity:	NOAEL	200	mg/kg	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1490	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3170	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitising
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): lymph nodes, liver, spleen
Aspiration hazard:						No

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral toxicity - Fixed Dose Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative

Germ cell mutagenicity:						OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Carcinogenicity:							No indications of such an effect.
Reproductive toxicity:	NOEL	1000	mg/kg bw/d	Rat		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Specific target organ toxicity - single exposure (STOT-SE):							No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):							No indications of such an effect.
Aspiration hazard:							No
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	1000	mg/kg bw/d	Rat		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	0,212	mg/l	Rat		OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	

Methanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on persons.
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for classification., Vapours
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Mild irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:				Mouse	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Symptoms:						abdominal pain, vomiting, headaches, gastrointestinal disturbances, drowsiness, visual disturbances, watering eyes, nausea, mental confusion

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Bondtec STP 75							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

  

Trimethoxyvinylsilane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	191	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	

12.1. Toxicity to daphnia:	NOEC/N OEL	21d	28	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	169	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	NOEC/N OEL	72h	>957	mg/l	Scenedesmus subspicatus		88/302/EC
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	51	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>2500	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

3-(trimethoxysilyl)propylamine							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>934	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	331	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	>1000	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	67	%		Regulation (EC) 440/2008 C.4-A (DETERMINATION OF 'READY' BIODEGRADABILITY - DOC DIE-AWAY TEST)	Not readily biodegradable, Analogous conclusion
12.3. Bioaccumulative potential:							No
12.4. Mobility in soil:							Slight
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		3400	mg/l	activated sludge		
Toxicity to bacteria:	EC10		13	mg/l	Pseudomonas putida		Analogous conclusion 5,75 h
Toxicity to bacteria:	EC50		43	mg/l	Pseudomonas putida		Analogous conclusion 5,75 h

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butylmalonate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to daphnia:	NOEC/N OEL	21d	2	µg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	LOEC/L OEL	21d	6,4	µg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.2. Persistence and degradability:		28d	1 - 2	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.1. Toxicity to algae:	EC50	72h	61	mg/l	Scenedesmus subspicatus		

Toxicity to bacteria:	IC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
-----------------------	------	----	------	------	------------------	--	--

Calcium carbonate								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	LC50	96h			Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	No observation with saturated solution of test material.	
12.1. Toxicity to daphnia:	EC50	48h			Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	No observation with saturated solution of test material.	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)		
12.1. Toxicity to algae:	NOEC/N OEL	72h	14	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)		
12.2. Persistence and degradability:							Not relevant for inorganic substances	
12.3. Bioaccumulative potential:							Not to be expected	
12.4. Mobility in soil:							n.a.	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))		
Toxicity to bacteria:	NOEC/N OEL	3h	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))		
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum	
Other organisms:	EC50	21d	>1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa	
Other organisms:	NOEC/N OEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Glycine max	
Other organisms:	NOEC/N OEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Lycopersicon esculentum	
Other organisms:	NOEC/N OEL	21d	1000	mg/kg dw		OECD 208 (Terrestrial Plants, Growth Test)	Avena sativa	
Other organisms:	EC50	14d	>1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)		
Other organisms:	NOEC/N OEL	14d	1000	mg/kg dw	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)		
Other organisms:	EC50	28d	>1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)		
Other organisms:	NOEC/N OEL	28d	1000	mg/kg dw		OECD 216 (Soil Microorganisms - Nitrogen Transformation Test)		

Water solubility:			0,01 66	g/l		OECD 105 (Water Solubility)	20°C
-------------------	--	--	------------	-----	--	--------------------------------	------

Methanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
Other information:	Log Pow		-				
12.5. Results of PBT and vPvB assessment			0,77				No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	154 00	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	96h	182 60	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	96h	220 00	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		284 00		Chlorella vulgaris		Not to be expected
Toxicity to bacteria:	IC50	3h	>10 00	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### For the substance / mixture / residual amounts

EC disposal code no.:  
 The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
 08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 E.g. suitable incineration plant.  
 E.g. dispose at suitable refuse site.

##### For contaminated packing material

Pay attention to local and national official regulations.  
 Empty container completely.  
 Uncontaminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.  
 15 01 10 packaging containing residues of or contaminated by hazardous substances

### SECTION 14: Transport information

#### General statements

14.1. UN number:	n.a.
<b>Transport by road/by rail (ADR/RID)</b>	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Classification code:	n.a.
LQ:	n.a.
14.5. Environmental hazards:	Not applicable
Tunnel restriction code:	
<b>Transport by sea (IMDG-code)</b>	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
Marine Pollutant:	n.a.
14.5. Environmental hazards:	Not applicable
<b>Transport by air (IATA)</b>	
14.2. UN proper shipping name:	
14.3. Transport hazard class(es):	n.a.
14.4. Packing group:	n.a.
14.5. Environmental hazards:	Not applicable
<b>14.6. Special precautions for user</b>	

Unless specified otherwise, general measures for safe transport must be followed.  
**14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code**  
 Non-dangerous material according to Transport Regulations.

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.2 Chemical safety assessment

Observe restrictions:  
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0 g/l

A chemical safety assessment is not provided for mixtures.

### SECTION 16: Other information

Revised sections: 8  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

#### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).  
 H226 Flammable liquid and vapour.  
 H302 Harmful if swallowed.  
 H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H332 Harmful if inhaled.  
 H372 Causes damage to organs through prolonged or repeated exposure.  
 H410 Very toxic to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic  
 Flam. Liq. — Flammable liquid  
 Acute Tox. — Acute toxicity - inhalation  
 Skin Irrit. — Skin irritation  
 Eye Dam. — Serious eye damage  
 Acute Tox. — Acute toxicity - oral  
 STOT RE — Specific target organ toxicity - repeated exposure

#### Any abbreviations and acronyms used in this document:

acc., acc. to according, according to  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EC European Community  
 ECHA European Chemicals Agency  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 PBT persistent, bioaccumulative and toxic  
 PE Polyethylene  
 PNEC Predicted No Effect Concentration  
 ppm parts per million  
 PVC Polyvinylchloride  
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)  
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.  
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)  
 SVHC Substances of Very High Concern  
 Tel. Telephone  
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods  
 VOC Volatile organic compounds  
 vPvB very persistent and very bioaccumulative  
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:  
**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.